

1

2

3

4

5




6

7

A

NOTES:

1. Insulation: 30% Glass Filled PBT, UL94V-0, Color Black
2. Contact : Brass
3. Current Rating: 3A Max
4. Dielectric Voltage: 1000V rms / 1 minute
5. Insulation Resistance: 1000M ohm Min.
6. Contact Resistance: 30m ohm Max.
7. Operating and Storage Temperature: -40°C ~ +105°C
- ③ 8. Mating Cycles: 10 Min.




Contact Point

AKSNT/x BLACK

Contact Area Plating: ③
 G: Gold Flash
 Z: Tinned

D

D



E

E

F

F

RoHS compliant
 Unit:mm

G

G

Scale	Free	Customer-No.	
TOLERANCE		ASSMANN WSW-No.	AKSNT/G BLACK
.X	±0.38		AKSNT/Z BLACK
.XX	±0.25		
.XXX	±0.13		
DIM	TOL	Drawing-No.	
X. °	±1°	ASS 1004 CO	rev03
Angle	TOL	Replace	SHEET
UNIT	mm		

Id.	Modification	Date	Name
③	Update	07.06.2013	Winnie
②	Update	27.07.2009	Rate
①	Drawn	03.03.2004	Hellwig

Date	Name
03.03.2004	Hellwig
07.06.2013	Winnie

ASSMANN WSW/ components	
-----------------------------------	--

1

2

3

4

5

6

7

H

H