

Wiha Vinyl Grip Pliers & Cutters

High Leverage Cable Cutters



[SHOP](#)

326 High Leverage Cable Cutters
 Sickle-shaped cutting edge to prevent cable movement when cutting. Fastened adjustable lay-on joint. Clean cutting edges for cutting multi strand copper or aluminum cables. Safety lock with opening spring. Special CV tool steel forging, hardened and tempered for maximum performance. Soft vinyl grips are oil & solvent resistant.

| Item | ↔ | ↔ | Max. | Max. | 🔒 | 🔒 |
|------------------|-----|------|------|------|------|-----|
| No. | mm | Inch | mm | Inch | Pkg. | wt. |
| 326 41 Z50017001 | 170 | 6.75 | 40 | 1.6 | 1 | .62 |
| 326 43 Z50023001 | 230 | 9 | 60 | 2.4 | 1 | .94 |

Diagonal Cutters



[SHOP](#)

326 Diagonal Cutters DIN ISO 5749
 Low wear lap joint, riveted and able to withstand high levels of load. Low force cutting action, clean cutting. Long life edge is achieved through additional induction hardening to approx. 60 HRC. Special CV tool steel hardened and tempered. For soft & medium hard wire. Soft vinyl grips.

| Item | ↔ | ↔ | Cutting Capacity | 🔒 | 🔒 |
|------------------|-----|------|------------------|------|-----|
| No. | mm | Inch | Copper AWG | Pkg. | wt. |
| 326 38 Z12014001 | 140 | 5.5 | #6 | 1 | .33 |
| 326 42 Z12016001 | 160 | 6.3 | #6 | 1 | .42 |
| 326 39 Z12018001 | 180 | 7.0 | #6 | 1 | .53 |

High Leverage Cutters



[SHOP](#)

326 High Leverage Cutters DIN ISO 5749
 Semi-circular. Low wear lap joint, riveted and able to withstand high levels of load. Low force action, clean cutting. Long life is achieved through additional induction hardening of cutting edge to 64 HRC. CV 60 special tool steel hardened and tempered. Soft vinyl grips

| Item | ↔ | ↔ | Cutting Capacity | 🔒 | 🔒 |
|------------------|-----|------|------------------|------|-----|
| No. | mm | Inch | Copper AWG | Pkg. | wt. |
| 326 46 Z16016001 | 160 | 6.3 | #6 | 1 | .42 |
| 326 49 Z16018001 | 180 | 7.0 | #5 | 1 | .50 |
| 326 52 Z16020001 | 200 | 8.0 | #4 | 1 | .55 |