

**Industrial Ethernet
IE-BI-LCD-MM-C**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



FO LC inserts for plug-in connectors ver.1 / 4 / 14

General ordering data

Type	IE-BI-LCD-MM-C
Order No.	1964420000
Version	LC insert, Bulkhead insert LC duplex, multimode
GTIN (EAN)	4032248649037
Qty.	10 pc(s).

Data sheet

**Industrial Ethernet
IE-BI-LCD-MM-C**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 16
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 14.9 g

Temperatures

Humidity	0...85 % rel. humidity	Operating temperature	-40 °C...70 °C
Storage temperature		Installation temperature	

Downloads

GOST Approval POCC
 DE.ME25.B01411.pdf

General data

Configuration	Connector and flange insert for variant 1, 4 and 14 housings	Connection 1	LC Duplex
Connection 2	LC Duplex	Description of article	Bulkhead insert LC duplex, multimode
Fibre type	Multimode	Housing main material	PBT diecast zinc
Humidity	0...85 % rel. humidity	Insertion loss	≤ 0.4 dB
Plugging cycles	1000	Protection degree	IP 67 with housing
Return loss (attenuation)	≥ 30 dB		

Standards

Connector standard IEC 61754-20

Classifications

ETIM 3.0	EC001121	ETIM 4.0	EC001121
ETIM 5.0	EC001121	ETIM 6.0	EC001121
UNSPSC	30-21-18-01	eClass 5.1	27-14-40-17
eClass 6.2	27-25-05-04	eClass 7.1	27-25-05-04

Approvals

Approvals



ROHS Conform

Data sheet

**Industrial Ethernet
IE-BI-LCD-MM-C**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 16
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Dimensioned drawing

